

# Safety Data Sheet Dolomite with Additives

## Section 1. Identification

**GHS product identifier:** Dolomite with Additives  
**Other means of identification:** Crushed Stone, Calcium Magnesium Carbonate, Aggregate  
**Relevant identified uses of the substance or mixture and uses advised against:** Dolomite may be used in the manufacture of bricks, mortar, cement, concrete, plasters, paving materials, and other construction materials. Dolomite aggregate may be distributed in bags, totes, and bulk shipments. No known recommended restrictions.

**Supplier's details:** 300 E. John Carpenter Freeway, Suite 1645  
 Irving, TX 75062  
 (972) 653-5500

**Emergency telephone number (24 hours):** CHEMTREC: (800) 424-9300

## Section 2. Hazards Identification

**GHS Classification:** CARCINOGENICITY – Category 1A  
 SPECIFIC TARGET ORGAN TOXICITY – Category 2  
 REPEATED EXPOSURE  
 SKIN CORROSION/IRRITATION – Category 2  
 EYE DAMAGE/IRRITATION – Category 2A

### GHS label elements

**Hazard pictograms:**



**Signal word:** Danger  
**Hazard statements:** May cause cancer  
 May cause damage to organs (lung) through prolonged or repeated exposure  
 Causes skin irritation  
 Causes serious eye irritation

**Precautionary statements:**

**Prevention:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wash any exposed body parts. Wear protective gloves/protective clothing/eye protection/face protection.

**Response:** If exposed or concerned: Get medical advice/attention. If on skin: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If in eyes: Rinse continuously with water for several minutes. Remove contact lenses, if present and easy to do.

**Storage:** Restrict or control access to stockpile areas (store locked up). Engulfment hazard: To prevent burial or suffocation, do not enter a confined space, such as a silo, bulk truck or other storage container or vessel that stores or contains aggregates without an effective procedure for assuring safety.

**Disposal:** Dispose of contents/container in accordance with local/regional/national/international regulations.

**Hazards not otherwise classified (HNOC):** None known

**Supplemental Information:** Respirable Crystalline Silica (RCS) may cause cancer. Dolomite is a naturally occurring mineral complex that contains varying quantities of quartz (crystalline silica). In its natural bulk state, dolomite is not a known health hazard. Dolomite may be subjected to various natural or mechanical forces that produce small particles (dust) which may contain respirable crystalline silica (particles less than 10 micrometers in aerodynamic diameter). Repeated inhalation of respirable crystalline silica (quartz) may cause lung cancer according to IARC and NTP; ACGIH states that it is a suspected cause of cancer. Other forms of RCS (e.g., tridymite and cristobalite) may also be present or formed under certain industrial processes.

## Section 3. Composition/information on ingredients

### CAS number/other identifiers

**Substance/mixture:** Dolomite with Additives

Ingredient name	%	CAS number
Dolomite	50 - 100	16389-88-1
Magnesium Carbonate	0 - 50	546-93-0
Calcium Oxide	> 1	1305-78-8
Crystalline Silica (Quartz)	> 1	14808-60-7

Any concentration shown as a range is to protect confidentiality or is due to process variation. There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section. These materials are mined from the earth. Trace amounts of naturally occurring elements might be detected during chemical analysis of these materials.

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

### Description of necessary first aid measures

<b>Eye Contact:</b>	Dust: Immediately flush with plenty of water for at least 15 minutes. Hold eyelids apart. Remove contacts if present and easy to do. Occasionally lift the eyelid(s) to ensure thorough rinsing. Beyond flushing, do not attempt to remove material from the eye(s). Get medical attention if irritation develops or persists.
<b>Inhalation:</b>	Dust: Move to fresh air. Call a physician if symptoms develop or persist.
<b>Skin Contact:</b>	Dust: Wash off with soap and water. Get medical attention if irritation develops or persists.
<b>Ingestion:</b>	Dust: Rinse mouth and drink plenty of water. Never give anything by mouth to an unconscious person. Get medical attention.

### Most important symptoms/effects, acute and delayed

Inhaling dust may cause discomfort in the chest, shortness of breath, and coughing. Prolonged inhalation may cause chronic health effects. This product contains crystalline silica. Prolonged or repeated inhalation of respirable crystalline silica liberated from this product can cause silicosis, and may cause cancer.

### Indication of immediate medical attention and special treatment needed, if necessary

<b>Notes to physician:</b>	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
<b>Specific treatments:</b>	Not Applicable
<b>Protection of first-aiders:</b>	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.
<b>General information:</b>	Pre-existing medical conditions that may be aggravated by exposure include disorders of the eye, skin and lung (including asthma and other breathing disorders). If addicted to tobacco, smoking will impair the ability of the lungs to clear themselves of dust.

See toxicological information (Section 11)

## Section 5. Fire-fighting measures

### Extinguishing media

<b>Suitable extinguishing media:</b>	Not flammable. Use fire-extinguishing media appropriate for surrounding materials.
<b>Unsuitable extinguishing media:</b>	None known.
<b>Specific hazards arising from the chemical:</b>	No unusual fire or explosion hazards noted. Not a combustible dust.

**Hazardous thermal decomposition**

**Products:** None known

**Special protective equipment for fire-fighters:**

Use protective equipment appropriate for surrounding materials. No specific precautions.  
**General fire hazards:** Contact with powerful oxidizing agents may cause fire and/or explosions (see section 10 of SDS). No unusual fire or explosion hazards.

## Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

Wear appropriate protective equipment and clothing during clean-up of materials that contain or may liberate dust.

### Methods and materials for containment, cleaning up and Environmental precautions

Spilled material, where dust is generated, may overexpose cleanup personnel to respirable crystalline silica-containing dust. Do not dry sweep or use compressed air for clean-up. Wetting of spilled material and/or use of respiratory protective equipment may be necessary. Avoid discharge of fine particulate matter into drains or water courses.

## Section 7. Handling and storage

### Precautions for safe handling

**Protective measures:**

Do not handle until all safety precautions have been read and understood. Keep formation of airborne dusts to a minimum. Provide appropriate exhaust ventilation at places where dust is formed. Do not breathe dust. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment.

**Advice on general occupational hygiene:**

Observe good industrial hygiene practices. Promptly remove dusty clothing and launder before reuse.

**Conditions for safe storage, including any incompatibilities:**

Avoid dust formation or accumulation.

## Section 8. Exposure controls/personal protection

### Control parameters

#### Occupational exposure limits:

- 1 – Value equivalent to OSHA formulas (29 CFR 1910.1000; 29 CFR 1917; 29 CFR 1918)
- 2 – Value also applies to MSHA metal/Non-Metal (1973 TLVs at 30 CFR 56/57.5001)
- 3 – OSHA enforces 0.250 mg/m<sup>3</sup> in construction and shipyards (CPL-03-00-007)
- 4 – Value also applies to OSHA construction (29 CFR 1926.55 Appendix A) and shipyards (29 CFR 1915.1000 Table Z)
- 5 – MSHA limit = 10 mg/m<sup>3</sup>

Ingredient name	Exposure limits
Particulates not otherwise classified (CAS SEQ250)	<p><b>ACGIH TLV (United States, 3/2012)</b> TWA: 3 mg/m<sup>3</sup>. Form: Respirable particles (2) TWA: 10 mg/m<sup>3</sup>. Form: Inhalable particles (2)</p> <p><b>OSHA PEL (United States, 6/2010)</b> PEL: 5 mg/m<sup>3</sup>. Form: Respirable fraction PEL: 15 mg/m<sup>3</sup>. Form: Total dust (4) TWA: 5 mg/m<sup>3</sup>. Form: Respirable fraction (1) TWA: 15 mg/m<sup>3</sup>. Form: Total dust (1, 4, 5)</p>
Calcium Oxide (CAS 1305-78-8)	<p><b>ACGIH TLV (United States, 3/2012)</b> TWA: 2 mg/m<sup>3</sup>.</p> <p><b>OSHA PEL (United States, 6/2010)</b> TWA: 5 mg/m<sup>3</sup>.</p> <p><b>NIOSH REL (United States, 6/2009)</b> TWA: 2 mg/m<sup>3</sup>.</p>
Crystalline Silica (Quartz) (CAS 14808-60-7)	<p><b>OSHA PEL (United States, 9/2017)</b> TWA: 0.3 mg/m<sup>3</sup>. Form: Total dust (1,2) TWA: 0.05 mg/m<sup>3</sup>. Form: Respirable (1,2,3)</p> <p><b>ACGIH TLV (United States, 3/2012)</b> TWA: 0.025 mg/m<sup>3</sup>. Form: Respirable fraction</p> <p><b>NIOSH REL (United States, 6/2009)</b> TWA: 0.05 mg/m<sup>3</sup>. Form: Respirable dust</p>

#### Appropriate engineering controls:

Good general ventilation (typically 10 air changes per hour indoors) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

#### Exposure guidelines:

OSHA PELs, MSHA PELs, and ACGIH TLVs are 8-hr TWA values. NIOSH RELs are for TWA exposures up to 10-hr/day and 40-hr/wk. Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled. Terms including "Particulates Not Otherwise Classified," "Particulates Not Otherwise Regulated," "Particulates Not Otherwise Specified," and "Inert or Nuisance Due" are often used interchangeably; however, the user should review each agency's terminology for differences in meanings.

#### Biological limit values:

No biological exposure limits noted for the ingredient(s)

### Individual protection measures

#### Hygiene measures:

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

#### Eye/face protection:

Wear safety glasses with side shields (or goggles).

#### Hand protection:

Use personal protective equipment as required.

#### Body protection:

Use personal protective equipment as required.

#### Other skin protection:

Use personal protective equipment as required.

#### Respiratory protection:

When handling or performing work that produces dust or respirable crystalline silica in excess of applicable exposure limits, wear a NIOSH-approved respirator that is properly fitted and is in

good condition. Respirators must be used in accordance with all applicable workplace regulations.

**Thermal hazards:**

Not anticipated. Wear appropriate thermal protective clothing if necessary.

## Section 9. Physical and chemical properties

### Appearance

<b>Physical State:</b>	Solid, particles of granular and angular mixture	<b>Lower and Upper explosive flammable limits</b>	Not applicable
<b>Color:</b>	Various colors, gray	<b>Vapor pressure:</b>	Not applicable
<b>Odor:</b>	Not applicable	<b>Vapor density:</b>	Not applicable
<b>Odor threshold:</b>	Not applicable	<b>Relative density:</b>	Not available
<b>pH:</b>	8.5	<b>Solubility:</b>	Not available
<b>Melting point:</b>	Not applicable	<b>Solubility in water:</b>	Insoluble
<b>Boiling point:</b>	Not applicable	<b>Partition coefficient: n-octanol/water:</b>	Not applicable
<b>Flash point:</b>	Non-combustible	<b>Auto-ignition temperature:</b>	Not applicable
<b>Burning time:</b>	Not applicable	<b>Decomposition temperature:</b>	730 °C
<b>Burning rate:</b>	Not applicable	<b>SADT:</b>	Not available
<b>Evaporation Rate:</b>	Not applicable	<b>Viscosity:</b>	Not applicable
<b>Flammability (solid, gas):</b>	Not applicable		

## Section 10. Stability and reactivity

<b>Reactivity:</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>Chemical Stability:</b>	Material is stable under normal conditions
<b>Possibility of hazardous reactions:</b>	No dangerous reaction known under conditions of normal use.
<b>Conditions to avoid:</b>	Avoid contact with strong oxidizing agents. Do not store or mix with fluorine, aluminum, magnesium, ammonium salts, hydrogen and acids.
<b>Incompatible materials:</b>	Strong acids. Crystalline silica may react violently with strong oxidizing agents, causing fire and explosions.
<b>Hazardous decomposition products:</b>	Silica dissolves in hydrofluoric acid producing a corrosive gas-silicon tetrafluoride.

## Section 11. Toxicological information

### Information on toxicological effects

<b>Acute toxicity:</b>	Not expected to be acutely toxic.
<b>Irritation/Corrosion:</b>	<b>Skin:</b> Dust: May cause irritation through mechanical abrasion. This product is not expected to be a skin hazard. <b>Eyes:</b> Direct contact with eyes may cause temporary irritation through mechanical abrasion. <b>Inhalation:</b> Repeated inhalation of respirable crystalline silica (quartz) may cause silicosis, a fibrosis (scarring) of the lungs. Silicosis is irreversible and may be fatal. Silicosis increases the risk of contracting pulmonary tuberculosis. Some studies suggest that repeated inhalation of respirable crystalline silica may cause other adverse health effects including lung and kidney cancer. <b>Ingestion:</b> Not likely due to product form. However accidental ingestion may cause discomfort.
<b>Sensitization:</b>	<b>Respiratory sensitization:</b> No respiratory sensitizing effects known. <b>Skin sensitization:</b> Not known to be a dermal irritant or sensitizer.
<b>Mutagenicity:</b>	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
<b>Aspiration Hazard:</b>	Not expected to be an aspiration hazard.
<b>Reproductive toxicity:</b>	Not expected to be a reproductive hazard.
<b>Symptoms related to physical, chemical and toxicological characteristics:</b>	Dust: discomfort in the chest. Shortness of breath. Coughing.
<b>Carcinogenicity:</b>	Respirable crystalline silica has been classified by IARC and NTP as a known human carcinogen, and classified by ACGIH as a suspected human carcinogen.

Product/ingredient name	OSHA	IARC	ACGIH	NTP
Crystalline Silica (Quartz) CAS 14808-60-7)	Not listed	1 Carcinogenic to humans	A2	Known to be human Carcinogen

**Specific target organ toxicity (acute exposure)**

Name	Category	Route of Exposure	Target Organs
Crystalline Silica (Quartz) CAS 14808-60-7)	-	Inhalation	Not reported to have effects

**Specific target organ toxicity (chronic exposure)**

Name	Category	Route of Exposure	Target Organs
Crystalline Silica (Quartz) CAS 14808-60-7)		Inhalation	May cause damage to organs (lung through prolonged or repeated exposure).

**Potential chronic health effects: General:** Prolonged inhalation of respirable crystalline silica may be harmful. May cause damage to organs (lungs) through prolonged or repeated exposure. There are reports in the literature suggesting that excessive crystalline silica exposure may be associated with autoimmune disorders and other adverse health effects involving the kidney. In particular, the incidence of scleroderma (thickening of the skin caused by swelling and the thickening of fibrous tissue) appears to be higher in silicotic individuals. To date, the evidence does not conclusively determine a causal relationship between silica exposure and these adverse health effects.

## Section 12. Ecological Information

### Ecotoxicity

May be toxic to aquatic life due to high pH in water. Discharging sand and gravel dust and fines into waters may increase total suspended particulate (TSP) levels that can be harmful to certain aquatic organisms.

**Persistence and degradability:** Not applicable.  
**Bioaccumulative potential:** Not applicable.  
**Mobility in soil:** Not applicable.  
**Other adverse effects:** No other adverse environmental effects (e.g., ozone depletion, photochemical ozone creation potential, global warming potential) are expected from this component.

## Section 13. Disposal considerations

**Disposal methods:** Do not allow fine particulate matter to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with fine particulates. Dispose of contents in accordance with local/regional/national/international regulations.

**Hazardous waste code:** Not regulated.

**Waste from residues/unused products:** Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner.

**Contaminated packaging:** Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty packaging materials should be recycled or disposed of in accordance with applicable regulations and practices.

## Section 14. Transportation information

	DOT Classification	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class(es)	-	-	-
Packing group	-	-	-
Environmental hazards	-	-	-
Additional information	-	-	-

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

## Section 15. Regulatory Information

### U.S. Federal regulations:

<b>OSHA Hazard Communication Standard, 29 CFR 1910.1200</b>	This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200
<b>TSCA Section 12(b) Export Notification (40 CFR 707, Subpart. D):</b>	Not regulated
<b>OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):</b>	Not listed
<b>CERCLA Hazardous Substance List (40 CFR 302.4):</b>	Not listed
<b>Clean Air Act Section 112 (b): Hazardous Air Pollutants (HAPs):</b>	Not regulated
<b>Clean Air Act Section 112 (r) Accidental Release Prevention (40 CFR 68.130):</b>	Not regulated
<b>Safe Drinking Water Act (SDWA):</b>	Not regulated

## SARA 311/312

**Classification:** Delayed (chronic) health hazard

**Composition/information on ingredients**

Name	%	Fire Hazard	Sudden release of pressure	Reactive	Immediate (acute) health hazard	Delayed (chronic) health hazard
Crystalline Silica (Quartz) CAS 14808-60-7	>1	No	No	No	No	Yes
Calcium Oxide CAS 1305-78-8	>1	No	No	No	Yes	No

## SARA 313 (TRI)

	Product name	CAS number	%
Form R-Report requirements	Crystalline Silica (Quartz)	14808-60-7	Not regulated

## State regulations

<b>Massachusetts RTK:</b>	Product listed
<b>New Jersey RTK:</b>	Product listed
<b>Pennsylvania RTK:</b>	Product listed
<b>Rhode Island RTK:</b>	Not regulated.

## California Prop. 65

WARNING: This product contains crystalline silica and chemicals (trace metals) known to the State of California to cause cancer.

Ingredient name	Cancer	Reproductive	No significant risk level	Maximum acceptable dosage level
Crystalline Silica (Quartz) CAS 14808-60-7	Yes	No	No	No

## International regulations

Ingredient name	CAS #	TSCA	Canada	WHMIS	EEC
Crystalline Silica (Quartz)	14808-60-7	Yes	DSL	D2A	EINECS
Magnesium Carbonate	546-93-0	Yes	DSL	-	EINECS
Dolomite	16389-88-1	Yes	NDSL	-	EINECS
Calcium Oxide	1305-78-8	Yes	NDSL	-	EINECS

WHMIS Classification:

D2A "Materials Causing Other Toxic Effects"



## Section 16. Other Information

Date of issue: 07/01/2018

Replaces: 06/01/2015

Revised Section(s): Section 8

### Notice to reader

While the information provided in this safety data sheet is believed to provide a useful summary of the hazards of dolomite as it is commonly used, the sheet cannot anticipate and provide all of the information that might be needed in every situation. Inexperienced product users should obtain proper training before using this product. In particular, the data furnished in this sheet do not address hazards that may be posed by other materials mixed with dolomite to produce dolomite products. Users should review other relevant material safety data sheets before working with this dolomite or working on dolomite products.

SELLER MAKES NO WARRANTY, EXPRESS OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE OR CONCERNING THE ACCURACY OF ANY INFORMATION PROVIDED BY Lehigh Hanson, except that the product shall conform to contracted specifications. The information provided herein was believed by the Lehigh Hanson to be accurate at the time of preparation or prepared from sources believed to be reliable, but it is the responsibility of the user to investigate and understand other pertinent sources of information to comply with all laws and procedures applicable to the safe handling and use of product and to determine the suitability of the product for its intended use. Buyer's exclusive remedy shall be for damages and no claim of any kind, whether as to product delivered or for non-delivery of product, and whether based on contract, breach of warranty, negligence, or otherwise shall be greater in amount than the purchase price of the quantity of product in respect of which damages are claimed. In no event shall Seller be liable for incidental or consequential damages, whether Buyer's claim is based on contract, breach of warranty, negligence or otherwise.



## Abbreviations

ACGIH — American Conference of Governmental Industrial Hygienists  
CAS — Chemical Abstract Service  
CERCLA — Comprehensive Emergency Response and Comprehensive Liability Act  
CFR — Code of Federal Regulations  
DOT — Department of Transportation  
GHS — Globally Harmonized System  
HEPA — High Efficiency Particulate Air  
IATA — International Air Transport Association  
IARC — International Agency for Research on Cancer  
IMDG — International Maritime Dangerous Goods  
NIOSH — National Institute of Occupational Safety and Health  
NOEC — No Observed Effect Concentration  
NTP — National Toxicology Program  
OSHA — Occupational Safety and Health Administration  
PEL — Permissible Exposure Limit  
REL — Recommended Exposure Limit  
RQ — Reportable Quantity  
SARA — Superfund Amendments and Reauthorization Act  
SDS — Safety Data Sheet  
TLV — Threshold Limit Value  
TPQ — Threshold Planning Quantity  
TSCA — Toxic Substances Control Act  
TWA — Time-Weighted Average  
UN — United Nations